



**PRODUCT:**

**Overview:**

Parkland™ PLAS-TEX® high-performance reclaimed architectural polymer replaces and exceeds traditional wood composite panel (MDF, laminate panels) specifications, performance and environmental properties.

**Handling:**

Parkland PLAS-TEX panels feature easy handling and fabrication and cut smoothly without dust. PLAS-TEX is fiberglass-free and handles without need for gloves, contains no dangerous fibers or chemicals, and cuts with ordinary field tools incl. Jigsaw, circular saw, and may be smoothed with a file and sandpaper.

**Cleaning and Chemical Resistance:**

PLAS-TEX performance exceeds glass and wood fiber panel performance for cleanability, waterproofness (absorption), impact resistance, and chemical resistance. PLAS-TEX is safe to clean with most strong chemicals including bleach.

**Specification:**

The PLAS-TEX tough 100% solid non-porous construction provides a tough VOC-free [1], cost-effective solution for architectural panels meeting G21 mold and mildew, and California Proposition 65 requirements.

**Custom Panels:**

Are available from Parkland, including clad one and two sides with nearly all commercially available finishes.

**APPLICATIONS & USES:**

PLAS-TEX is ideal for high-performance environmental panel cores in feature walls, furniture, and other primary spaces, and as a stand-alone cost-effective wall panel solution for service areas and wash-out rooms. Use PLAS-TEX anywhere exposed to high-moisture, impacts, wet areas, and other areas exposed to high traffic and abuse

**PARKLAND PLAS-TEX® & LEED:** Products can qualify for LEED points under MR 5.1, 5.2, & IEQ section 4.1.

**PLAS-TEX FEATURES:**

- 100% solid construction
- 100% VOC-free and fiberglass-free, waterproof, low-maintenance product.
- PLAS-TEX Products do not support the growth of mold, mildew or bacteria, and PASS G-21.
- Best-in-class chemical & impact resistance.

**Warranty**

- All PLAS-TEX products carry a one year exclusive non-prorated warranty.

**Product Availability**

Thickness	Texture	Available Colors	Panel Size**	Installation	Available Accessories
1/4" 3/8" 1/2" 5/8"	Matte	Bright White Almond Grey Black	4' x 8'	Mechanically Fastened Over Drywall or Studs	Monochrome Moldings
	Cracked-Ice		4' x 10' 4' x 12'		

[1] VOCs below detectable limits – none detectable VOC materials able to be found.  
\*\*1/4"-4' x 8', 10', 12' / 3/8"-4' x 8', 10' x 12', 1/2"-4' x 8', 10' / 5/8"-4' x 8'.



**PHYSICAL PROPERTIES:**

ASTM D-4060	Taber Abrasion (wear resistance)	.060 wear index (varies by surface)
ASTM D-732 [1]	Shear Strength	2970 psi
ASTM D-696 [1]	Coefficient / Therm. Expansion	3.84 X 10 <sup>5</sup> in/in/°F
ASTM D-790 [1]	Flexural Modulus (psi)	90,460 +/- 2840 psi
ASTM D-3029 [1]	Gardner Impact 23°C	22.60 in. lb.
ASTM D-570 [1]	Water Absorption	0.055%
ASTM D-790 [1]	Flexural Modulus (psi)	78,240 +/- 3,940 psi
ASTM D2240 [1]	Hardness	51 Shore D
ASTM D-792 [1]	Specific Gravity	1,15
ASTM D-649 [1]	Heat Distortion Temperature	51.30°C
ASTM D-256 [2]	Un-notched Izod Impact	7.02 +/- 0.21 ft lb/in
ASTM D-695 [2]	Compressive Strength	5293 psi
ASTM D-638 [2]	Elongation @ Ultimate (psi)	5293 psi
ASTM D-638 [1]	638 [2] Tensile Strength @ ultimate (psi)	410 +/- 10%
ASTM D-882 [1]	882 [3] Elongation @ Break (%)	1190 +/- 60 psi
ASTM D-882 [1]	882 [3] Tensile Strength @ Break	(%) 2062 +/- 179 psi

1-PLAS-TEX 0.090" sheet thickness, 2- PLAS-TEX 0.100" sheet thickness, 3- PLAS-TEX 0.060" sheet thickness, 4- PLAS-TEX-FR .090". NEMA results based on the NEMA LD 3-2000.

**PLAS-TEX® Specifications**

- 1. Parkland PLAS-TEX** wall panels defined as: Non-porous, solid waterproof polymer alloy wall panels maintaining the same composition throughout the part, featuring integral reinforcement, pigments, and high performance modifiers, and meeting applicable building materials standards; NEMA, UL, ANSI, ASTM, NFPA, and California Proposition 65 and having minimum physical, performance, and environmental properties specified.
- 2. Panel Finish:**  
PLAS-TEX is available in a variety of textures and colors. Panel backside and edges may possess slight imperfections that do not adversely affect performance or physical properties and are not cause for rejection.

**Panel Dimensions:**

**Thickness:**

- 1/4", 3/8", 1/2", 5/8" thick

**Width:** 48" +/- 1/8" **Length:** 96, 120", 144" +/- 3/8"

**Approvals & Certifications, PLAS-TEX:**

- Compliant with California Proposition 65.
- Mold & Mildew Resistant per ASTM D3273-94 and D3274-95 tests, and passes standard G21.

**\*\*NOTE TO SPECIFIER \*\*** Parkland™ PLAS-TEX® installations provide a unique combination of features including waterproof VOC-free composition, extreme chemical and impact resistance, and best-in-class cleanability.

**GENERAL:**

**Storage & Preparation** – Carefully inspect all panels prior to installation. Notify Parkland at once for any unacceptable materials. PLAS-TEX panels should be stored indoors on a flat, clean, dry surface for at least 48 hours prior to installation.

**Serviceable Temperature Range** – PLAS-TEX panels shall maintain performance characteristics and physical properties in temperatures ranging from 40°F to 140°F. PLAS-TEX may discolor near heat sources.

**Parkland PLAS-TEX Advantage** – PLAS-TEX significantly outperforms ordinary wall panels.

**Cleaning Guidelines** – When a regular cleaning schedule is executed, soil and dirt will not build up. Use a mild, non-abrasive cleaner such as soapy water or ammonia-based cleaners.

**Accessories:** Color-matched monochrome poly moldings and Parkland SPECTRATILE® ceilings make the perfect complement to PLAS-TEX panels.

**For Additional Information, see:**

- Parkland PLAS-TEX Sell Sheet
- Parkland NRP/NRP-FR/ULTRA/POLYWALL CSI Specifications
- Parkland NRP-PLAS-TEX Use & Care Guide
- Parkland NRP/NRP-FR/ULTRA/DÉCOR/POLYWALL Warranty

For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Prices, specifications, and product information are presented in good faith and believed correct at time of printing, and are subject to change without notice. Colors, sizes and product images are for general reference use only, are approximate, and variations may occur in printing and/or production. Parkland™ Plastics and its affiliates do not warrant the accuracy or timeliness of any information contained in any product document and have no liability for any errors or omissions in such. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT(S) TO WHICH INFORMATION REFERS. Statements expressed in this technical bulletin represent our best judgment based on our experience and are recommended for the installation of Parkland™ products under normal conditions. Unless prior approval is obtained in writing from Parkland™, any deviation from these recommended procedures shall be at the sole risk of the installer. Carefully inspect all parts. If a part is defective, notify Parkland at once. Failure to do so shall be at the sole risk of the installer.

