

### PRODUCT:

#### Overview:

Parkland™ DURO-LAM™ Polymer clad engineered wood panels exceed ordinary agricultural and construction panels. The 100% polymer surface will not rot, chip, or crack.

#### Handling:

Parkland DURO-LAM panels feature easy handling and fabrication. DURO-LAM is 100% fiberglass-free and handles without need for gloves, contains no dangerous fibers or chemicals, and cuts with ordinary field tools incl. Jigsaw, circular saw, and may be smoothed with a file and sandpaper.

#### Cleaning and Chemical Resistance:

DURO-LAM performance exceeds most other panel's performance for cleanability, impact resistance, and chemical resistance. DURO-LAM is safe to clean with most strong chemicals including bleach.

#### Specification:

The DURO-LAM tough 100% solid non-porous construction provides a tough VOC-free<sup>[1]</sup>, cost-effective solution for insulative panels meeting California Proposition 65, and G21 mold and mildew and requirements.

### APPLICATIONS & USES:

DURO-LAM is ideal for animal confinement and general use in uninsulated buildings and weather-protected spaces in agricultural and commercial construction. Use DURO-LAM anywhere exposed to moisture, impacts, chemicals, and other areas exposed to high traffic and abuse\*.

Parkland DURO-LAM™ & LEED: Products can qualify for LEED points under MR 4.1, 4.2, 5.1, 5.2, & IEQ section 4.1.

#### DURO-LAM Features:

- 100% solid waterproof cladding
- 100% VOC-free and fiberglass-free
- DURO-LAM surface does not support the growth of mold, mildew or bacteria.
- Best-in-class chemical & impact resistance

#### Warranties:

- DURO-LAM products carry a one year exclusive non-rated warranty.

#### Other Products:

- DURO-LAM Lite: 5/16" thick panels
- DURO-LAM Lite-FR: 7/16" thick

### Product Availability

Thickness	Product	Texture	Available Colors	Fire Rating**	Panel Size	Installation	Available Accessories
15/32"	DURO-LAM	Matte, Smooth, Cracked-Ice	White	Class-C	4' x 8'	Mechanically Fastened to Studs or Wall	1 and 2-piece Monochrome Moldings
5/16"	DURO-LAM Lite	Various	Various		4' x 10'		
7/16"	DURO-LAM Lite FR	Various	Various	Class-A			

[1] VOCs below detectable limits – none detectable VOC materials able to be found.

\*\* Per ASTM E-84 Steiner Tunnel testing for flame spread and smoke developed.

\*For use in moist environments, be sure to caulk all seams and moldings to prevent moisture from getting to the wood behind the panel.

### 1. DURO-LAM Specifications:

**Parkland DURO-LAM** wall panels defined as: Non-porous, waterproof reclaimed polymer alloy-clad wall panels featuring integral wood composite reinforcement, pigments, and high performance characteristics, and meeting applicable building materials standards; NEMA, UL, ANSI, ASTM, NFPA, and California Proposition 65 and having minimum physical, performance, and environmental properties specified.

### 2. DURO-LAM Finish:

DURO-LAM is available in white and a variety of textures, and DURO-LAM Lite and DURO-LAM Lite-FR are available in a variety of colors and textures. Panel backside and edges may possess slight imperfections that do not adversely affect performance or physical properties and are not cause for rejection.

### 3. DURO-LAM Dimensions:

- DURO-LAM: 15/32"      ■ DURO-LAM Lite FR: 7/16"
- DURO-LAM Lite: 5/16"

**Width:** 48" +/- 1/8", **Length:** 96, 120", +/-1/4"

### Approvals & Certifications, DURO-LAM:

- Compliant with California Proposition 65

**\*\*NOTE TO SPECIFIER \*\*** Parkland™ DURO-LAM™ installations provide a unique combination of features including waterproof VOC-free surface, extreme chemical and impact resistance, and best-in-class cleanability.

### GENERAL:

**Storage & Preparation** – Carefully inspect all panels prior to installation. Notify Parkland at once for any unacceptable materials. DURO-LAM panels should be stored on a flat, clean, dry surface for at least 48 hours prior to installation.

**Serviceable Temperature Range** – Parkland DURO-LAM panels shall maintain performance characteristics and physical properties in temperatures ranging from -40°F to 140°F. DURO-LAM panels may discolor near heat sources.

**Accessories** – Color-matched 1-piece and 2-piece monochrome poly moldings make the perfect complement to DURO-LAM panels.

**Cleaning Guidelines** – When a regular cleaning schedule is executed, soil and dirt will not build up. Use a mild, non-abrasive cleaner such as soapy water or ammonia-based cleaners.

### For Additional Information, see:

Parkland DURO-LAM Sell Sheet

Parkland DURO-LAM/DLMLITE/DLMLITEFR  
CSI Specifications

Parkland DURO-LAM/DLMLITE/DLMLITEFR  
Use & Care Guide

For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Prices, specifications, and product information are presented in good faith and believed correct at time of printing, and are subject to change without notice. Colors, sizes and product images are for general reference use only, are approximate, and variations may occur in printing and/or production. Parkland™ Plastics and its affiliates do not warrant the accuracy or timeliness of any information contained in any product document and have no liability for any errors or omissions in such.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT(S) TO WHICH INFORMATION REFERS.

