



### USE:

DURO-LAM™ panels are recommended for interior wall applications and are designed to be fastened direct to studs and columns in buildings and agricultural structures. DURO-LAM Lite panels are applied to substrates such as sealed concrete block, plywood or drywall. These panels are intended to have a long life cycle, the length of which will depend on the rigors of the environment, the abuse sustained, and the level of maintenance.

### ROUTINE CARE:

DURO-LAM panels feature a tough factory-laminated finish over an engineered wood or composite core. They are extremely resistant to impact, staining, and chemicals, and may be cleaned or scrubbed with most commercially available cleaning products. If the panels have been installed following the installation guide for a water resistant system, the panels can be hosed down or pressure washed. Follow the recommendations below to clean the surface properly. Always test an inconspicuous area first.

### ROUTINE CLEANING:

Parkland™ DURO-LAM products guaranteed safe to be cleaned with the following commercially available cleaners.

- Soapy Water
- Mild Detergent Solutions
- Formula 409® All Purpose Cleaner
- Fantastik® Oxypower® Multi-Purpose Cleaner
- Kaboom® with OxiClean Stain Fighter
- Clorox Green Works® Natural Bathroom Cleaner\*
- Windex® Multi-Surface Cleaner with Vinegar
- Clorox® Anywhere® Hard Surface™ Daily Sanitizing Spray

Tip: Wipe dry after cleaning to prevent a build-up of soap residue, which can create the appearance of light scratches over time

DURO-LAM products are well-suited to most recognized sanitizing procedures. Contact Parkland for more information.

### APPEARANCE RETENTION:

Parkland DURO-LAM panels are made for demanding environments. Whether for wainscoting for a casual dining restaurant, wall protection for a loading dock area, or paneling for animal confinement, the panels are designed to withstand the abuse. This provides outstanding appearance retention and a long life cycle for an excellent value proposition.

### AVOID:

Some strong chemicals are not compatible with DURO-LAM products; contact Parkland for more information on compatible chemicals. Surfaces exposed to strong chemicals should be promptly flushed with water as contact for even a short period of time may discolor or damage product.

For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Windex®, Formula 409®, Fantastik®, Kaboom® and Clorox® are registered trademarks; Parkland™ Plastics makes no claim of affiliation to trademark holders. The information contained in this Technical Bulletin is given by Parkland™ Plastics free of charge. It is based upon technical data which Parkland believes to be reliable and is intended for use by persons having knowledge of this technical area at their own discretion and risk. Seller assumes no responsibility for results obtained or damage incurred from the use of this technical bulletin either in whole or in part by a buyer of Parkland wall panel products.

