



Put up the studs, put up the panels, and finish the wall—no waiting!

- Install over metal or wooden studs
- No dust, no mess, no drywall!
- Fire resistant--up to 1-hour fire rating
- Waterproof surface laminate: FRP, Vinyl, Metal, HPL
- Save money and time
- Excellent for Renovation or new construction
- 3/8" or 1/2" thick panels



Parkland Performance™

WALLS & CEILINGS

CLASS A **ENHANCED** PERFORMANCE

FAÇADE panels offer exceptional durability in a 3-layer composite construction: Decorative PLAS-TEX® surface, fireproof ceramic core, and a high strength plywood substrate. FAÇADE panels completely eliminate the need for gypsum wall board and the mudding, sanding, and clean-up that the installation involves. Direct-to-Stud installation is accomplished with a unique adhesive that permanently bonds the panel to wood or metal studs. Special 2-part moldings conceal mechanical fasteners where the panels join and at the corners to give

the panels a smooth, finished appearance. DUROBASE protective moldings offer further wall protection in colors that harmonize with the panels--or provide a decorative accent. What could be easier? Wall studs, finished panels and protective moldings in one continuous operation-- a finished room in days rather than weeks!

See our video for easy installation steps.

FEATURES & BENEFITS

100% WATERPROOF LAMINATE

- QUICK INSTALLATION
- Non-absorbent
- Attach directly to studs
- No Water Damage with frequent wash down with sealed panels

EXCEPTIONAL PROPERTIES IN A STRUCTURAL PANEL

- CLASS A FIRE RATING!
- Structural strength of wood allows for anchoring that would not be possible with drywall
- Perfect for new builds and renovation
- 1/2" thick panel with sizes up to 48" x 144"
- 2 PC Divider Molding covers up seams between panels quickly and provides for beautiful finish
- Inside Corner / Outside Corner Moldings for Complete System



LAMINATE IS CHEMICALLY RESISTANT

- Impervious to most chemicals
- Use cleaners of all types without damage
- No yellowing or color change with corrosive environments
- Unaffected by petroleum products

PRODUCT USES

- Added partition walls in factories, stores, and offices
- Renovation
- Warehouses
- Medical facilities
- Plant offices
- Commercial kitchens
- Retail stores
- Modular classrooms, offices, and medical facilities

PRODUCT SPECIFICATIONS

PROPERTY	TEST METHOD	UNIT	VALUE
Flexural Strength	ASTM D790	PSI	3,988
Flexural Modulus	ASTM D790	PSI	668,000
Tensile Strength	ASTM D638	PSI	1,412
Tensile Modulus	ASTM D638	PSI	491,079
Izod Impact	ASTM D256	ft.lb/in.	4.86
Taber Abrasion	ASTM D4060	Wear Cycles	0.060 Wear Index
Stain Resistance	ASTM D1308		No Effect
Shore D	ASTM D2240	Durometer	65
Cleanability	ASTM D1308		10
Flame Spread	ASTM E-84		15
Smoke Developed	ASTM E-84		250



Parkland Performance™
WALLS & CEILINGS