

USE:

NRP-FR, NRP DÉCOR, and NRP-ULTRA products glue over appropriate drywall subwalls for interior decorative wall applications in commercial interiors including wet areas and impact areas. NRP-FR and NRP-ULTRA meet the ASTM E-84 Class-A flame and smoke performance. Other restrictions and information may be found in the **Installation Guide, and CSI Specification**. Follow all instructions and recommendations prior to installation.

ROUTINE CARE:

NRP-FR, NRP DÉCOR*, and NRP-ULTRA products feature a factory finish to protect and beautify the surface. For lightly textured products extra care is recommended to prevent mars or scratches from occurring. Products are 100% waterproof and may be cleaned or scrubbed with water-based cleaners and most commercially-available cleaning products. Follow the recommendations below in order to properly clean the surface. Always test in an inconspicuous area first.

ROUTINE CLEANING:

Parkland™ NRP products guaranteed safe to be cleaned with the following commercially available cleaners.

- Soapy Water
- Mild Detergent Solutions
- Formula 409® All Purpose Cleaner
- Fantastik® Oxypower® Multi-Purpose Cleaner
- Kaboom® with OxiClean Stain Fighter
- Clorox Green Works® Natural Bathroom Cleaner*
- Windex® Multi-Surface Cleaner with Vinegar
- Clorox® Anywhere® Hard Surface™ Daily Sanitizing Spray

Tip: Wipe dry after cleaning to prevent a build-up of soap residue, which can create the appearance of light scratches over time.

Parkland decorative NRP products are well-suited to most recognized sanitizing procedures. Follow instructions set forth by governing body and test in an inconspicuous area first. Contact Parkland for more information.

APPEARANCE RETENTION:

Parkland decorative NRP products provide best-in-class appearance retention. NRP-FR, NRP DÉCOR, and NRP-ULTRA products are intended to have a long service life and may be scrubbed by hand with a soft cloth and non-abrasive cleaner.

AVOID:

Some strong chemicals are not compatible with NRP-FR, NRP DÉCOR, and NRP-ULTRA products; contact Parkland for more information on compatible chemicals. Surfaces exposed to strong chemicals should be promptly flushed with water as contact for even a short period of time may discolor or damage product.

For more information call: 800.835.4110 • or Visit: www.parklandplastics.com

Windex®, Formula 409®, Fantastik®, Kaboom® and Clorox® are registered trademarks; Parkland™ Plastics makes no claim of affiliation to trademark holders. The information contained in this Technical Bulletin is given by Parkland™ Plastics free of charge. It is based upon technical data which Parkland believes to be reliable and is intended for use by persons having knowledge of this technical area at their own discretion and risk. Seller assumes no responsibility for results obtained or damage incurred from the use of this technical bulletin either in whole or in part by a buyer of Parkland wall panel products.

*Waterproof properties may vary by panel facing material selected.

