ARCHITECTURAL GRADE WALL SYSTEM™ Use & Care Guide

ROUTINE CARE

Most Parkland™ Architectural Grade Wall System™ products feature a textured finish to help protect and beautify the surface. For smooth finishes, extra care is recommended in handling and cleaning the surface to prevent mars or scratches from occurring. Soapy water, ammonia-based cleaners or common household surface cleaners will remove most dirt and residue from products. Please note that while all Parkland wall panel products are extremely resistant to water, they are not intended for pressure washing or heavy hose-type cleaning. Stubborn residue will require a little stronger cleaner. Follow the recommendations below, in order, to properly clean your wall panel product. Always test in an inconspicuous area first.

STAIN REMOVAL:

- Warm soapy water, wipe with damp cloth
- Ammonia based liquid cleaner
- Tip: Wipe dry after cleaning to prevent a build-up of soap residue, which can create the appearance of light scratches over time.

ROUTINE CLEANING:

Soapy Water

- Formula 409® Glass & Surface Cleaner
- Mild Detergent Solutions
- Windex® Multi-Surface Cleaner

RESTORATION:

Parkland NRP®-clad panel surfaces may be repaired or restored in some cases.

- Dinged edges may be restored with medium or fine sandpaper or a laminate file, follow up with fine sandpaper, and a White 3M Scotch-Brite® pad.
- Scratches or mars may be buffed out in some cases by wet-sanding with 220-600 grit paper, in multiple steps. Polish with toothpaste, Armor-All® or car polish, and rinse.
- For damaged panels, detach and replace as per Parkland-specified procedures.

SANITIZING:

Parkland A.G. Panels are amenable to sanitizing procedures including the use of mild bleach solutions. Follow Sanitizing instructions set forth by governing body, and test one tile first to check result. Contact Parkland for more information.

AVOID:

The use of non-recommended cleaners may cause surface damage and should not be used on A.G. Wall System surfaces. Some chemicals are not compatible with wall panel products, avoid contact with: Chloroform, Ketones, strong bleach solutions, acid-based cleaners, and other harsh chemicals. Surfaces exposed to these agents should be promptly flushed with water. Contact for even a short period of time can cause surface damage, spots, or discoloration. Follow the recommended restoration procedures described above as needed to its original condition. Severe damage caused by incompatible chemical contact will require product replacement. Do not place hot appliances on or very near or proximity with all Parkland wall panel surfaces without contacting Parkland first.

For more information call: 800.835.4110 • or Visit: www.parklandplastics.com

Windex®, Formula 409®, Scotch-Brite® and Armor-All® are registered trademarks; Parkland Plastics™ makes no claim of affiliation to trademark holders.

Prices, specifications, and product information are presented in good faith and believed correct at time of printing, and is subject to change without notice. Colors, sizes and product images are for general reference use only, are approximate, and variations may occur in printing and/ or production. Parkland Plastics™ and its affiliates do not warrant the accuracy or timeliness of any information contained in any product document and have no liability for any errors or omissions in such.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT(S) TO WHICH INFORMATION REFERS.



© 2010 Parkland Plastics™ PPAWUCR AP07142010