



## **PART 1 — GENERAL**

### **1.1 RELATED DOCUMENTS**

- A. Drawings and general provisions of the contract, including general and supplementary conditions and Division 1 Specification Sections, apply to this Section.

### **1.2 SUMMARY**

- A. This Section includes the following: Wall Panels composed of 100% non-porous polymer surface over dense material mineral alloy for superior performance without sacrificing cleanability
  1. Commercial wall panels [4' x 8', 4' x 10'].
  2. Installation.
- B. Related Sections include the following:
  1. Attachment Parkland™ LEED Compliance for potential LEED applicability.
  2. Division 9 Section "Wall Panels".

### **1.3 DEFINITION**

- A. Parkland™ MagnaWall panels are a waterproof polymer laminate surface on both sides of a core composition of high density, VOC-free, compressed mineral and industrial fiber alloy construction, maintaining the same composition throughout the part.
- B. Appearance: Monochromatic colored panel.

### **1.4 SUBMITTALS**

- A. Product data:
  1. MagnaWall water-resistant mineral alloy wall panels.
    - a. Chemical resistance, no effect with:
      - 1) Soapy Water
      - 2) Detergent Solution
      - 3) Ammonia-based cleaners
      - 4) Isopropyl Alcohol
      - 5) Bleach
- B. Installer instruction requirements:
  1. Show location of areas where wall panels are to be installed.
    - a. Commercial installations: Show locations and sizes of cutouts, panel seams, and holes for fixtures, and other items installed in any wall panels.
- C. Samples:
  1. For each wall panel product specified.
    - a. Manufacturer will supply minimum 4-inch by 4-inch sample in specified finish.
    - b. Indicate full range of color.
  2. Approved samples will be retained by manufacturer as a standard for work.
- D. Product data:
  1. Product description, installation information and compliance with specified performance requirements to be agreed upon prior to receipt of order.
- E. LEED submittals:
  1. MR Credit 5.1 and 5.2 Regional Materials: [All finishes].
    - a. Product weight for MagnaWall standard product: are 1.0 Lb./ S.F.
    - b. Product origin: Middlebury, Indiana.
- F. Product certificates:
  1. Signed manufacturer's statement of compliance available upon request with each purchase order.
- G. Fabricator/installer qualifications:
  1. Panel installation requires no training.
- H. Maintenance data:
  1. Use and Care Guide available upon request.



### 1.5 QUALITY ASSURANCE QUALIFICATIONS

**A.** Applicable standards:

1. Standards of the following, as referenced herein:

- a. American National Standards Institute (ANSI)
- b. American Society for Testing and Materials (ASTM)
- c. Underwriters Laboratories (UL)

2. Fire test response characteristics:

- a. Provide with the following Class A (Class I) surface burning characteristics as determined by testing identical products per UL 723 (ASTM E84) or another testing and inspecting agency acceptable to authorities having jurisdiction:

- 1) Flame Spread Index: 15 (Class-I)
- 2) Smoke Developed Index: 250 (Class-I)

### 1.6 DELIVERY, STORAGE AND HANDLING- Manufacturer will:

- A.** Deliver no components to project site until areas are ready for installation.
- B.** Store components indoors prior to installation.
- C.** Handle materials to prevent damage to finished surfaces.

### 1.7 WARRANTY

**A.** Provide manufacturer's warranty against defects in materials.

- 1. Warranty shall provide material to repair or replace defective materials.
- 2. Damage caused by physical or chemical abuse or damage from excessive heat or abrasion will not be warranted.
- 3. Warranty shall be non-transferable to subsequent owners.

**B.** Manufacturer's Warranty Period:

- 1. Five years from date of purchase.

### 1.8 MAINTENANCE

- A.** Routine and regular cleaning with soapy water.
- B.** Removal of stains with common household cleansers, and a small amount of cleaning solution in a rag for very stubborn stains. See **NRP Use & Care Guide** for more information.

## PART 2 — PRODUCTS

### 2.1 MANUFACTURER

- A. Parkland Plastics™**  
104 Yoder Drive  
Middlebury, INDIANA  
46540 USA  
1-800-835-4110

### 2.2 MATERIAL PROPERTIES

**A.** Description:

- 1. Parkland™ MagnaWall is a high-density magnesium mineral alloy with one-side lamination of waterproof polymer front surface meeting applicable building materials standards:  
ASTM/ ion chromatography analysis, having minimum physical and performance properties specified.

- a. Thickness: 0.125" [1/8"] - 0.500" (1/2")
- b. Sizes: 4' x 8', and 4' x 10'

## 2.2 MATERIAL PROPERTIES (continued)

### B. Performance characteristics:

#### 1. MagnaWall

ASTM E-84	Flame spread	15
ASTM E-84	Smoke Development	Less than 250
Specific Gravity	Pounds/ SF	0.82
ASTM D-3273	Mold Resistance	10 [best]
Ion Chromatography	VOC Content	0
Ion Chromatography	Corrosive Content	0

## 2.3 Institutional Affiliations and Approvals

- A. Complete NAHB stain testing results available.
- B. UL-Passes E-84, Class-I

## 2.4 Material Qualifications

- A. Does not support the growth of mold or mildew.
- B. All products 100% fiberglass-free
- C. All products VOC-free
- D. All products free of corrosive materials.

## 2.5 Accessories, Adhesives, and Sealant

- A. Moldings, Sealbond 105

## 2.6 Finishes- Select from manufacturer's available standard and custom

- A. Color:
  - 1. White
- B. Finish [pattern]:
  - 1. Pebbled
  - 2. Other finishes available by special order.

## PART 3 — EXECUTION [Installation process]

### 3.1 EXAMINATION

- A. Upon request, manufacturer will assist customer, with installer present, to examine supporting fixtures with installer present for compliance with requirements.
- B. Installers to proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 INSTALLATION: Installer will:

- A. Install wall panels on approved substrate or in track style systems in accordance with approved specifications.
  - 1. Finish any cut edges for a workmanlike appearance with fine sandpaper.
  - 2. Remove surface residue and clean entire surface.

### 3.3 CLEANING AND PROTECTION

- A. Keep components clean during installation, or clean and cover with protective covering.
- B. Remove adhesives, sealants and other stains.

### 3.4 SCHEDULE

- A. Wall Panels:
  - a. Pattern \_\_\_\_\_ Color Pebbled White \_\_\_\_\_

## ARCHITECT'S SPECIFICATION:

### **Parkland™ MagnaWall Architectural Specification:**

Wall Panels shall be of high-pressure magnesium mineral alloy with one-side lamination of waterproof polymer surface. Wall Panels shall be water-resistant, and not support the growth of mold or mildew, and shall have a Class-I fire rating.

### **Approved manufacturer:**

**Parkland Plastics™**  
**104 Yoder Drive**  
**Middlebury, INDIANA 46540**

Color to be: Pebbled White

For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Prices, specifications, and product information are presented in good faith and believed correct at time of printing, and is subject to change without notice. Colors, sizes and product images are for general reference use only, are approximate, and variations may occur in printing and/or production. Parkland Plastics™ and its affiliates do not warrant the accuracy or timeliness of any information contained in any product document and have no liability for any errors or omissions in such.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT(S) TO WHICH INFORMATION REFERS.

