



**Pre-constructed wall panels
assure performance and
simplify installation.**

When you need the structural strength of wood with the surface durability and performance qualities of a fiberglass-free plastic outer skin, DURO-LAM Panels simplify the matter on a wide variety of commercial wall applications. And because the panels are constructed using recycled materials, they help you stay Green.

The bright white wall surface, with a choice of cracked ice/pebbled, matte, or smooth finish, brightens surroundings and reduces lighting cost of a variety of commercial applications such as convenience stores, food processing plants, factories, retail stores or animal housing facilities.



Parkland Performance™
WALLS & CEILINGS



WOOD **ENHANCED** PERFORMANCE

DURO-LAM™ combines the structural strength of wood and the exceptional durability of a non-fiberglass plastic skin.

Our unique PLAS-TEX® sanitary wall covering is permanently bonded to oriented strand board (OSB) or plywood, making it rigid and easy to install using mechanical fasteners or cartridge style construction adhesive. The PLAS-TEX surface, of course, is totally waterproof and will not support bacteria, mold or mildew.



FEATURES & BENEFITS

100% WATERPROOF LAMINATE

- Non-absorbant
- Bacteriostatic surface
- Mold and mildew resistant
- Available in 3 textures on OSB or plywood
- No water damage with frequent wash-down if panels are sealed

EXCEPTIONAL PROPERTIES IN A STRUCTURAL PANEL

- Structural strength of wood enhanced by the water and chemical resistance of a thick plastic skin
- Excellent for renovation
- 3/8" plywood in sizes up to 48"x120"
- Dual lamination available for panels where both sides are visible

LAMINATE IS CHEMICALLY RESISTANT

- Impervious to most chemicals
- Use cleaners of all types without damage
- No yellowing or color change with corrosive environments
- Unaffected by petroleum products

PRODUCT USES

- Animal confinement
- Food processing
- Commercial kitchens and restaurants
- Industrial wall coverings
- Portable classrooms and offices

PRODUCT SPECIFICATIONS - LAMINATE ONLY

PROPERTY	TEST METHOD	UNIT	VALUE
Water absorption	ASTM D570	%	.055
Compressive strength	ASTM D695	psi	5293
Coefficient of lineal thermal expansion	ASTM D696	in/in/degree F	N/A
Flexural modulus	ASTM D790	psi	78,000 +/- 3,800
Shore hardness	ASTM D2240	D scale	51
Dart drop impact strength	ASTM D3029	inch-pounds	21 @ 71° F

STANDARD PRODUCT RANGE*

SIZE	FINISH	COLOR	PCS PER UNIT
On Plywood 5/16" x 48" x 96"	Matte & Cracked-Ice	Bright White	50
5/16" x 48" x 120"	Matte & Cracked-Ice	Bright White	50
3/8" x 48" x 96"	Matte & Cracked-Ice	Bright White	25
On OSB 3/8" x 48" x 120"	Matte & Cracked-Ice	Bright White	25
On Plywood or OSB by Special Order	Smooth	Bright Whites	

*Other thicknesses, colors and lengths available by special order.