

MAGNATILE™ CEILING TILES



*Flame spread: 0 Smoke: 0**

*Perfect for the Most
Demanding Jobs*



- Mold/Mildew Resistant
- VOC-Free
- Not Damaged by Water
- Washable & Scrubbable
- .65 NRC
- LEED Applicable: 5.1 & 5.2



Parkland Performance™
WALLS & CEILINGS

MAGNATILE™ CEILING TILES

LEED APPLICATION

Product	MR Credit 5 Regional Materials	IEQ Credit 4.1 Low Emitting Materials	Weight/S.F.	Weight/S.F. Acoustic-II
MagnaTile	Middlebury, IN up to 2 points	up to 1 point	1 lb.	0.9lb.

MAGNATILE FEATURES

- Easily Sanitized
- Class A
- Moisture resistant
- No VOC's
- Resists mold, mildew, and bacteria growth
- Recyclable
- No Dust
- Gasketing not required in most medical installations.

MagnaTile™ is tested to zero flame spread and smoke development-will not burn, and is available in acoustic, textured and custom finishes. MagnaTile features no corrosive or noxious materials, does not support the growth of mold or mildew, is VOC-free, washable, and 5-year warranted.

INSTALLATION


Use skill saw to cut to size, cut with the back of the tile up, and place Waterproof Ceiling Tiles into PVC or aluminum grid system. Optional clips may be used to clamp tiles down for uneven grid systems. To cut holes use a 1/2" diameter or larger hole saw to form radius corners. Waterproof Ceiling Tiles are nominally sized 2'x2' and 2'x4', but can also be trimmed using utility knife. When using the tiles in clean room or similar environments, reseal cut edges with tape.

MagnaTile Applications:

Restaurants, kitchens-commercial, clean rooms, laboratories, research facilities, hotels & motels, public buildings, schools, hospitals and nursing homes.



Staccato



Acoustic-II

MAGNATILE PROPERTIES

ASTM E-84	Flame spread	0
ASTM E-84	Smoke Development	0
Weight	Pounds/ SF	1.0
ASTM D-3273	Mold & Mildew Resistance [1-10]	10 [best]
ASTM D-256	NRC coefficient	.55 [acoustic]
Ion Chromatography	VOC Content	0
Ion Chromatography	Corrosive Content	0

PRODUCT AVAILABILITY

Finish	Noise Reduction Coefficient	Color	Fire Rating	Tile Size	Packaging
Staccato	Not Rated	Matte White	Class I	2' x 2' 2' x 4'	12 pc/ case (48 SF) 10 pc/ case (80 SF)
Custom Finishes*	Not Rated				
Acoustic II	.55				

*Special order

5 YEAR LIMITED WARRANTY

For Additional Information, see: CSI Specifications, Ceiling Tile Product Overview Guide, Ceiling Tile Use & Care Guide.

Prices, specifications, and product information are presented in good faith and believed correct at time of printing, and is subject to change without notice. Colors, sizes and product images are for general reference use only, are approximate, and variations may occur in printing and/ or production. Parkland Plastics™ and its affiliates do not warrant the accuracy or timeliness of any information contained in any product document and have no liability for any errors or omissions in such.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT(S) TO WHICH INFORMATION REFERS.

Statements expressed in this technical bulletin represent our best judgment based on our experience and are recommended for the installation of Parkland™ products under normal conditions. Unless prior approval is obtained in writing from Parkland™, any deviation from these recommended procedures shall be at the sole risk of the installer. Carefully inspect all parts. If a part is defective, notify Parkland™ at once. Failure to do so shall be at the sole risk of the installer.

For more information call: 800.835.4110 • or Visit: www.parklandplastics.com

