PLAS-TEX® WALL PANELS



PLAS-TEX® POLYWALL™ & NRP® WALL PANELS

POLYWALL/MATTE TEXTURE

Thickness: .060" Bright White, Almond*

4' x 8', 10'



Thickness: .090" Bright White, Almond*

4' x 8', 10'





FEATURES:

- 100% waterproof
- Fiberglass-free
- · Does not support mold, mildew, or bacteria growth
- Chemically inert
- Color goes all the way through
- Made from 100% recycled resins
- USDA compliant, CFIA approved

BENEFITS:

- Non-absorbent: no swelling, rotting or water discoloration
- No irritating, harmful fiberglass dust
- Hygienic: does not contribute to "sick building syndrome"
- Not affected by acids, harsh chemical solvents or petroleum products
- For interior use
- Scratches don't show
- Extended product life
- Passes most interior building codes
- Suitable for use in federally inspected food processing plants

PLAS-TEX® THICK PANELS

THICK PANELS

Thicknesses: 1/4" - 5/8"
Bright White Matte
1/4" x 4' x 8', 10', 12'
3/8" x 4' x 8', 10', 12'
1/2" x 4' x 8', 10'

5/8" x 4' x 8'

Bright White Cracked-Ice, Almond Cracked-Ice and Almond Matte are available by Special Order


PLAS-TEX® WALL PRODUCT **STRUCTURAL VARIATIONS**

The environmentally friendly and absolutely unique PLAS-TEX® surface is also available in structural variations that incorporate a wide range of substrate materials depending on application. DURO-LAM™ Panels, for example, incorporate OSB or lightweight plywood substrate and can be installed directly over studs.

DURO-THERM™ panels feature PLAS-TEX® permanently bonded to a polypropylene fluted substrate that reduces preparation and installation costs by eliminating taping, mudding and sanding. This lightweight, easy-to-install wall system also provides an impressive R3 insulation value.



DURO-LAMTM



DURO-THERM™





