SPECTRATILE® CEILING TILE



SPECTRATILE® DÉCOR

All the great features of SPECTRATILE DÉCOR:


- Decorative options include metallics and woodgrains
- Complies with building codes requiring 1 pound per square foot to avoid lifting
- Passes Class A 1-hour fire rated available



SPECTRATILE DÉCOR is not yet GREENGUARD Certified or UL Classified.

100% WATERPROOF CEILING TILE

It's a truly spectacular lay-in ceiling that stays that way, day after day... year after year. With an extended product life and one year warranty, it's a permanent, low maintenance solution to common lay-in ceiling problems. It's non-absorbent and will not swell, bow or rot. It won't harbor bacteria and it's mold and mildew resistant. It can be scrubbed and even pressure washed. There are no special coatings or surface sealants needed to resist stains or withstand harsh conditions. SPECTRATILE. It's every bit as spectacular as it sounds. See for yourself at www.parklandplastics.com.



SPECTRATILE Tiles Can Save Money on Lighting, With Their Excellent **Light Reflectance Values**

100% WATERPROOF

- · No water damage or staining
- Non-absorbent, no swelling, bowing or rotting
- · Will not harbor bacteria
- · Mold and mildew resistant

FUNCTIONAL

- Class A, per ASTM E-84
- Passes UL1715 room corner burn test
- NRC for the acoustic tile is .52
- GREENGUARD Certified

COST EFFECTIVE

- · Extended product life
- Permanent replacement solution
- · Improve and reduce your overhead
- Low maintenance

LIGHT REFLECTANCE

 Finalé 85%

 Millennium 81%

Repertoire

82%

PRODUCT COMPARISON CHART

FEATURES	SPECTRATILE	VINYL-CLAD GYPSUM-CORE	FIBER-BASED TILE
Zero Water Absorbance	х		
Guaranteed Against Water Stains	х		
Resists Mold, Mildew, Bacteria Growth	х	Х	
Perfect Score for ASTM Mold Resistance Test	Х		
Will Not Flake, Break or Create Dust	х		
Impact Damage Resistant	х		
May be Pressure Washed or Scrubbed	х	Х	
Sound Absorbent			х
Decorative Patterns	х		х
Passes IBC 2603.9	х		

In the chart to the left, SPECTRATILE is compared to data obtained for traditional ceiling tiles that are commonly available at retail outlets. The comparisons are general in nature and do not refer to any specific manufacturer's products. The comparisons are based upon independent tests and various manufacturers' published product specifications.



SPECTRATILE USE AND CARE

SPECTRATILE can be installed in a standard grid. Even the SPECTRATILE DÉCOR is light enough that the grid and hanging system will ordinarily not have to be replaced.

It can be cut with a circular saw and in some cases with a utility knife. For tight cuts use a jig saw or a Rotozip.

It can be taken down and washed without damage, and since SPECTRATILE is non-absorbent it can be power washed. Most strong cleaners like Simple Green® will not damage the surface, but it is always best to try an inconspicuous corner first.

Complete care and maintenance instructions are available on www.parklandplastics.com.

SPECTRATILE PROPERTIES

ASTM E-84	Flame Spread	25 or Less
ASTM E-84	Smoke Development	Less than 450
Weight	Pounds/SF	.6
ASTM D 3273	Mold/Mildew Resistance	1-10 / 10 Best
Ion Chromatography	VOC Content	0
Ion Chromatography	Corrosive Content	0



^{*}Fissured pattern is printed on the tile.