

### USE:

INSULEX or INSULEX-FR are ideal for insulated ceilings in food areas, wet areas, and service areas in restaurants, food processing facilities, and for walls and ceiling in cold storage warehouses. Use INSULEX-FR in building areas exposed to high-moisture, impacts, and regular cleaning or scrubbing. INSULEX-FR may also increase light reflectance to improve interior brightness, and cleanliness as a result of various reflective and sanitary finish options. INSULEX-FR Panels are made with a tough engineered polymer face permanently laminated over a 1" or 2" foam core. INSULEX-FR panels are designed to be fastened directly to ceiling joists or wall 16"- 24" on center. They are also available in 24" x 24" and 24" x 48" ceiling panels which fit a standard grid. Other restrictions and information may be found in the *Installation Guide, and CSI Specification*. Follow all instructions and recommendations prior to installation.

### ROUTINE CARE:

INSULEX-FR products exceed mineral fiber insulation performance for cleanability, waterproofness (absorption), impact resistance, and chemical resistance. INSULEX-FR panels are rigid, lightweight, and waterproof. All INSULEX-FR panels are extremely resistant to impact, staining, condensation, and mold and mildew growth. INSULEX-FR panels may be cleaned or scrubbed with water and most commercially available cleaning products. Use the recommend cleaning products below, in order, to properly clean the surface. Always test in an inconspicuous area first.

### ROUTINE CLEANING:

Parkland™ INSULEX-FR products guaranteed safe to be cleaned with the following commercially available cleaners.

- Soapy Water
- Mild Detergent Solutions
- Formula 409® All Purpose Cleaner
- Fantastik® OxyPower® Multi-Purpose Cleaner
- Kaboom® with OxiClean Stain Fighter
- Clorox Green Works® Natural Bathroom Cleaner\*
- Windex® Multi-Surface Cleaner with Vinegar
- Clorox® Anywhere® Hard Surface™ Daily Sanitizing Spray

Tip: Wipe dry after cleaning to prevent a build-up of soap residue, which can create the appearance of light scratches over time.

INSULEX-FR products are well-suited to most recognized sanitizing procedures. Follow instructions set forth by governing body and test in an inconspicuous area first. Contact Parkland for more information.

### APPEARANCE RETENTION:

Parkland INSULEX-FR products are most often laminated with a PLAS-TEX® or other long service life material, they have excellent resistance to abrasion and scratching, and best-in-class appearance retention.

### AVOID:

Some strong chemicals are not compatible with INSULEX-FR products; contact Parkland for more information on compatible chemicals. Surfaces exposed to strong chemicals should be promptly flushed with water as contact for even a short period of time may discolor or damage product.

For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Windex®, Formula 409®, Fantastik®, Kaboom® and Clorox® are registered trademarks; Parkland™ Plastics makes no claim of affiliation to trademark holders. The information contained in this Technical Bulletin is given by Parkland™ Plastics free of charge. It is based upon technical data which Parkland believes to be reliable and is intended for use by persons having knowledge of this technical area at their own discretion and risk. Seller assumes no responsibility for results obtained or damage incurred from the use of this technical bulletin either in whole or in part by a buyer of Parkland wall panel product.

