



#### USE:

DURO-THERM™ products are recommended for insulation and thermal barrier use in wall applications in agricultural buildings, refrigeration rooms, and special cold environment uses. They also work well as wall panels in buildings subjected to extreme temperature variations, like car washes. Panels 15/32" or thicker are designed to be fastened direct to studs 16" on center. DURO-THERM Lite is a thinner-gauge panel for covering rough walls or concrete block without leveling or repairing the wall. Other restrictions and information may be found in the **Installation Guide, and CSI Specification**. Follow all instructions and recommendations prior to installation.

#### ROUTINE CARE:

DURO-THERM products feature a tough PLAS-TEX® laminate and a fluted plastic core, making the panels, stiff, light weight, and waterproof. All DURO-THERM products are extremely resistant to impact, staining, condensation, and mold and mildew growth. DURO-THERM panels may be cleaned or scrubbed with water and most commercially-available cleaning products. Use the recommend cleaning products below, in order, to properly clean the surface. Always test in an inconspicuous area first.

#### ROUTINE CLEANING:

Parkland™ DURO-THERM products guaranteed safe to be cleaned with the following commercially available cleaners.

- Soapy Water
- Mild Detergent Solutions
- Formula 409® All Purpose Cleaner
- Fantastik® Oxypower® Multi-Purpose Cleaner
- Kaboom® with OxiClean Stain Fighter
- Clorox Green Works® Natural Bathroom Cleaner
- Windex® Multi-Surface Cleaner with Vinegar
- Clorox® Anywhere® Hard Surface™ Daily Sanitizing Spray

Tip: Wipe dry after cleaning to prevent a build-up of soap residue, which can create the appearance of light scratches over time

DURO-THERM products are well-suited to most recognized sanitizing procedures.  
Contact Parkland for more information.

#### APPEARANCE RETENTION:

Parkland DURO-THERM products are most often laminated with a PLAS-TEX sheet .060" thick. Since this sheet is homogeneous it has excellent resistance to abrasion and scratching, better than most other high performance wall coverings including FRP. This leads to best-in-class appearance retention and excellent product life.

#### AVOID:

Some strong chemicals are not compatible with DURO-THERM products; contact Parkland for more information on compatible chemicals. Surfaces exposed to strong chemicals should be promptly flushed with water as contact for even a short period of time may discolor or damage product.

For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Windex®, Formula 409®, Fantastik®, Kaboom® and Clorox® are registered trademarks; Parkland™ Plastics makes no claim of affiliation to trademark holders. The information contained in this Technical Bulletin is given by Parkland™ Plastics free of charge. It is based upon technical data which Parkland believes to be reliable and is intended for use by persons having knowledge of this technical area at their own discretion and risk. Seller assumes no responsibility for results obtained or damage incurred from the use of this technical bulletin either in whole or in part by a buyer of Parkland wall panel products.

