



**Pre-constructed wall panels  
assure performance and  
simplify installation.**

DURO-LAM™ is a pre-constructed wall panel created by laminating PLAS-TEX® to the surface of either OSB or Plywood. When you need the structural strength of wood with a durable, easy to clean surface, DURO-LAM is the panel for you. Install directly to steel or wooden studs, and complete your project in no time at all.

DURO-LAM is available in various colors and textures. DURO-LAM is also available with a Class A Fire Rating per the ASTM E-84. This product is called DURO-LAM FR. DURO-LAM can brighten surroundings, reduce required lighting, and is the perfect wall panel for a variety of commercial applications such as convenience stores, food processing plants, factories, retail stores, and animal housing facilities.





# WOOD ENHANCED PERFORMANCE

DURO-LAM™ combines the structural strength of wood with the exceptional durability of a top layer of PLAS-TEX®

laminate. DURO-LAM has a Class C Fire Rating per the ASTM E-84, but is also available with a Class A Fire Rating - DURO-LAM-FR\*\*. For applications where a solid substrate is already present, DURO-LAM LITE and DURO-LAM LITE-FR (Class A Fire Rating) are the perfect solution to a quickly installed durable barrier on your walls! The panels are rigid and will not flex with studs placed 16" or 24" on center. They are easy to install using our 2-piece molding system and mechanical fasteners, or our specially designed adhesive. A waterproof construction is easily achieved by using a silicone caulk to seal the joints. All of the mechanical fasteners can be hidden using our innovative method of installation! Create a beautiful wall system in no time at all!



## FEATURES & BENEFITS

### 100% WATERPROOF LAMINATE

- Non-absorbent surface
- Mold and mildew resistant
- Available in 3 textures on OSB or plywood
- Easy to install

### EXCEPTIONAL PROPERTIES IN A STRUCTURAL PANEL

- Structural strength of wood enhanced by the water and chemical resistance of a thick plastic skin
- Excellent for renovation
- Dual lamination available for panels where both sides are visible

### LAMINATE IS CHEMICALLY RESISTANT

- Impervious to most chemicals
- Use cleaners of all types without damage
- No yellowing or color change with corrosive environments
- Unaffected by petroleum products

### PRODUCT USES

- Animal confinement
- Food processing
- Commercial kitchens and restaurants
- Industrial wall coverings
- Portable classrooms and offices

## PRODUCT SPECIFICATIONS - LAMINATE ONLY

PROPERTY	TEST METHOD	UNIT	VALUE
Compressive strength	ASTM D695	psi	5293
Coefficient of lineal thermal expansion	ASTM D696	in/in/degree F	N/A
Flexural modulus	ASTM D790	psi	78,000 +/- 3,800
Shore hardness	ASTM D2240	D scale	51
Dart drop impact strength	ASTM D3029	inch-pounds	21 @ 71° F
Surface flame spread and smoke development	ASTM E84	NA	Class A or Class C

## STANDARD PRODUCT RANGE\*

SIZE	FINISH	COLOR	PCS PER UNIT
On Plywood Class A 7/16" X 48" X 96" 7/16" X 48" X 120"	Matte, Cracked-Ice, Smooth	White	25
	Matte, Cracked-Ice, Smooth	White	25
Class C 3/8" x 48" x 96" 3/8" x 48" x 120"	Matte, Cracked-Ice, Smooth	White	25
	Matte, Cracked-Ice, Smooth	White	25
On OSB Class A 5/8" x 48" x 96" 5/8" x 48" x 120"	Matte, Cracked-Ice	White	25
	Matte, Cracked-Ice	White	25
On OSB Class C 15/32" x 48" x 96" 15/32" x 48" x 120"	Matte, Cracked-Ice	White	25
	Matte, Cracked-Ice	White	25

\*Other thicknesses, colors and lengths available by special order.

\*\*Call Parkland for product range details.

P.O. Box 339, 104 Yoder Drive, Middlebury, IN 46540 • Toll Free: 800.835.4110 • Phone: 574.825.4336 • www.parklandplastics.com

