

## PRODUCT OVERVIEW:

**Parkland™ POLYMAX WAINSCOT®** planks feature 100% waterproof solid polymer construction to provide designers the opportunity to create a unique space. Reversible tongue and groove planks can be installed vertically, horizontally, or diagonally. Sold in an attractive finished white, the POLYMAX WAINSCOT® Planks and optional Chair Rail / Base Molding can be painted to complement surrounding walls and furnishings.

**POLYMAX WAINSCOT®** features 100% solid polymer alloy construction. The entire system, including planks, chair rails and base moldings, are water-proof, washable, and are mold and mildew resistant. The easy tongue & groove installation means that many projects can be finished in a weekend.

**POLYMAX WAINSCOT®** is ideal for use to cover solid substrates (either walls or ceilings) in dining rooms, bathrooms, 4-Season rooms, hallways, or other areas in homes, restaurants, hotels, or any area needing elegant enhancing where the use of wood is problematic.

### Product Availability:

- 6-pack - 1/4" x 6" x 36" - 6 planks per package; Installed coverage 9 sq. ft., 3 linear
- 3-pack - 1/4" x 6" x 96" - 3 planks per package; Installed coverage 12 sq. ft., 1.5 linear feet
- Matching Chair Rail & Baseboard - 1 each Chair Rail and 1 each Baseboard per kit.
  - Chair Rail: 2.5" x 96"
  - Baseboard: 3.5" x 96"

### POLYMAX WAINSCOT® Features

- 100% solid polymer construction for 100% waterproof, washable, scrubbable low-maintenance product.
- Does not support the growth of mold, mildew, or bacteria.
- Tiles are 100% fiberglass-free, corrosive-free, and VOC-free.
- Highly light reflective Pre-finished White.
- Interior/Exterior Use
- Paintable - Use Oil Based or Acrylic Paint
- Non-combustible

### Warranties:

All POLYMAX products carry a one year limited warranty.

**Storage & Preparation** – Carefully inspect all planks, rails, and baseboard prior to installation. Notify Parkland™ at once for any unacceptable materials. Parkland POLYMAX should be stored indoors on a flat, clean, dry surface for at least 24 hours prior to installation.

**Serviceable Temperature Range** – Parkland ceiling tiles shall maintain its performance characteristics and physical properties in temperatures ranging from 14° F to 140° F. POLYMAX may discolor near heat sources.

**Accessories** – Parkland's POLYWALL™, NRP®, and NRP-FR wall systems make the perfect complement to POLYMAX WAINSCOT®.

**Cleaning Guidelines** – With regular cleaning, soil and dirt will not build up. Use a mild, non-abrasive cleaner such as soapy water or ammonia-based cleaners.

### For Additional Information, see:

- Parkland POLYMAX Sell Sheet
- Parkland POLYMAX Features & Benefits Planning Guide
- Parkland POLYMAX Installation Guide
- Parkland POLYMAX Warranty



For more information call: 800.835.4110 • or Visit: [www.parklandplastics.com](http://www.parklandplastics.com)

Prices, specifications, and product information are presented in good faith and believed correct at time of printing, and are subject to change without notice. Colors, sizes and product images are for general reference use only, are approximate, and variations may occur in printing and/or production. Parkland™ Plastics and its affiliates do not warrant the accuracy or timeliness of any information contained in any product document and have no liability for any errors or omissions in such.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT(S) TO WHICH INFORMATION REFERS.

