



USE:

PLAS-TEX® NRP® / POLYWALL™, is made from recycled polyolefin resins. NRP-FR is created by using polyvinyl chloride compounds to attain the Class A Fire Rating per the ASTM E-84. These resins are very inert and resist attack by most harsh chemicals, including many acids and solvents. Since these panels are the same composition all the way through they are very tough and resist marring, abrasion, and impact. They are recommended for interior wall applications in wet areas, impact areas, and for general wall protection. Panels 5/16" and thicker may be fastened directly to studs, otherwise panels glue over appropriate drywall subwalls. Other restrictions and information may be found in the **Installation Guide, and CSI Specification**. Follow all instructions and recommendations prior to installation. All NRP products are designed for a long service life.

ROUTINE CARE:

NRP, POLYWALL, and NRP-FR products are the same all the way through, making them very tough, and extremely durable. These panels may be cleaned or scrubbed with most commercially available cleaning products. Follow the recommendations below, in order, to properly clean the surface. Always test in an inconspicuous area first.

ROUTINE CLEANING:

Parkland™ NRP products guaranteed safe to be cleaned with the following commercially available cleaners.

- Soapy Water
- Mild Detergent Solutions
- Formula 409® All Purpose Cleaner
- Fantastik® OxyPower® Multi-Purpose Cleaner
- Kaboom® with OxiClean Stain Fighter
- Clorox Green Works® Natural Bathroom Cleaner*
- Windex® Multi-Surface Cleaner with Vinegar
- A rag damp with a small amount of acetone, MEK, or mineral spirits
- Clorox® Anywhere® Hard Surface™ Daily Sanitizing Spray

Tip: Wipe dry after cleaning to prevent a build-up of soap residue, which can create the appearance of light scratches over time.

NRP, POLYWALL, and NRP-FR products are well-suited to most recognized sanitizing procedures. Follow instructions set forth by governing body and test in an inconspicuous area first. Contact Parkland for more information.

APPEARANCE RETENTION:

Parkland NRP, POLYWALL, and NRP-FR products provide best in class appearance retention. They have an extended service life even in the most demanding environments to provide excellent life-cycle costs.

AVOID:

Some strong chemicals are not compatible with NRP, POLYWALL, and NRP-FR products; contact Parkland for more information on compatible chemicals. Surfaces exposed to strong chemicals should be promptly flushed with water as contact for even a short period of time may discolor or damage product.

For more information call: 800.835.4110 • or Visit: www.parklandplastics.com

Windex®, Formula 409®, Fantastik®, Kaboom® and Clorox® are registered trademarks; Parkland™ Plastics makes no claim of affiliation to trademark holders. The information contained in this Technical Bulletin is given by Parkland™ Plastics free of charge. It is based upon technical data which Parkland believes to be reliable and is intended for use by persons having knowledge of this technical area at their own discretion and risk. Seller assumes no responsibility for results obtained or damage incurred from the use of this technical bulletin either in whole or in part by a buyer of Parkland wall panel product.

